L Number	Hits	Search Text	DB	Time stamp
1	89018	gui ((graphical user) adj1 interface)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/09/11 17:18
2	706	(gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/09/11 17:21
3	349	((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) and (wireless wml html http)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/09/11 17:24
4	138	((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) and ((remote client portable) adj1 (computer workstation))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/09/11 17:26
5	7	((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) with ((remote client portable) adj1 (computer workstation))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/09/11 17:29
6	121	((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) with (computer workstation)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/09/11 17:30
7	92	(((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) with (computer workstation)) and ((((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) and (wireless wml html http)) (((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) and ((remote client portable) adj1 (computer workstation))))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/09/11 17:30
8	31	(((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) with (computer workstation)) and (((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) and (wireless wml html http)) and (((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) and ((remote client portable) adj1 (computer workstation)))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/09/11 17:40
9	61	((((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) with (computer workstation)) and ((((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) and (wireless wml html http)) (((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) and ((remote client portable) adj1 (computer workstation))))) not ((((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) with (computer workstation)) and (((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) and (wireless wml html http)) and (((gui ((graphical user) adj1 interface)) with (transmi$5 send$3) with (descri$5 ident$7)) and ((remote client portable) adj1 (computer workstation))))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/09/11 17:40

DOCUMENT-IDENTIFIER: US 20030086119 A1

TITLE: Print data transfer system, method of transferring print data, and computer program product to effect the method

---------- KWIC ---------

Detail Description Paragraph - DETX (36):
[0084] In this embodiment, the user interface data provided in the receiver computer 100 is not only for the transmitter computer 200 but generally for a large number of transmitter computers (for example, the transmitter computer main body 401 shown in FIG. 2) connected to the Internet 600. The user interface data thus mainly consists of **HTML** data written in **HTML**.

Detail Description Paragraph - DETX (37):
[0085] The Internet 600 is in the environment where different machine types coexist. It is accordingly difficult for the receiver computer 100 to identify the machine type of each transmitter computer connected to the Internet 600. In the case where the user interface data is created according to a program that depends upon a specific machine type and is supplied to the respective transmitter computers, some transmitter computers can not naturally utilize the user interface data. It is, however, practically

impossible to provide the
user interface data for each machine type and supply the user interface data
suitable for the machine type of each transmitter computer. This embodiment
accordingly creates the user interface data by utilizing the **HTML** that does not
depend upon any specific machine type and facilitates creation of the data.

Detail Description Paragraph - DETX (38):

[0086] The user interface data may be written in a computer language that
does not depend upon any specific machine type, for example, JAVA, instead of
the **HTML**.

Detail Description Paragraph - DETX (39):

[0087] In the transmitter computer 200, when the communications device 260
receives the transmitted user interface data, the transmission control unit 211
stores the user interface data into the hard disk 270, while the display
processing unit 213 displays a user interface for inputting the print settings
information on the display screen of the monitor 250, based on the user
interface data at step S106. As mentioned above, the user interface data is
HTML data and thus readily displayed by using a known Web browser software.

Detail Description Paragraph - DETX (55):

[0103] In this embodiment, the user interface data supplied from the
receiver computer 100 to the transmitter computer 200 is mainly written in the

HTML that does not depend upon any specific machine type. The **user interface** data usable by the **transmitter computer** 200 can thus be transferred to the **transmitter computer** 200, without requiring the receiver **computer** 100 to **identify** the machine type of the **transmitter computer** 200.

Detail Description Paragraph - DETX (56):

[0104] Since the user interface data is **HTML** data, a mechanism for calling a software component to utilize a CGI (Common Gateway Interface) function on the receiver computer 100 may be set in the user interface data. This mechanism enables the transmitter computer 200 to remote control the functions of the receiver computer 100. When the CPU 210 in the transmitter computer 200 has a low processing ability but the CPU 110 in the receiver computer 100 has a high processing ability, the transmitter computer 200 places the processing in the of the receiver computer 100 to ensure the high-performance processing.